

Executone Date and Time

Change Time

Lift the handset. Dial tone is heard.

Dial 28 and the four digit time in 24 hour clock format. Enter the HHMM (military time). Confirmation tone is heard.

Go Back to Menu

Change Date

Executone CX 816

- From station 100, take the handset off-hook.
- Dial "*".
- Dial "7764" (PROG).
- Press the "FLASH" button.
- Dial "28".
- Enter time and date as follows:
YYMMDDHHMMSS.
- Press the "HOLD" button.

Enter time and date in the following formats-

Year (YY) =00-99

Month (MM) =01-12

Day (DD) =0-31

Hour (HH) =00-24

Minute (MM) =00-60

Second (SS) =00-60

Executone Infostar VX II Voice Mail

- Press "SPKR" or lift handset.
Press "436" to enter voice mail.
- Press the "#" key, mailbox
"5000", press password "5000"
(default on most systems, yours
may differ) then the "#" key.
- Press "5" to change time and date.
- After the current date plays, enter

the current date MM:DD:YY.

- After the time plays, enter the new time HH:MM:SS in military format.
- When finished, press the "*" key until you hear "exiting the system".

Executone Isoetec IDS via Operator's Phone M-32 Series

The TIME option must be enabled on the system.

- Lift the handset or press the release key.
- Dial "28" and the four digit time in 24-hour clock format (military time). For example, to set the time as 3:00 pm, dial "281500". Confirmation tone is played.

Executone Isoetec IDS via Operator's Terminal **The TIME option must be enabled on the system.**

While the terminal is idle, press and hold Ctrl and "C". Release both keys. The cursor moves to the Hour field.

Enter the 2-digit hour in 24-hour clock format (ie., 16 for 4pm). The cursor moves to the Minutes field.

Enter the 2-digit minutes. The cursor moves back to the Hour field.

Press the Return key. The cursor moves to the Month field.

Enter the 2-digit month, day and year. The system inserts the "-" automatically.

Press and hold Ctrl and "C". Release.

Executone Isoetec Medley

Time

Press the "Menu" key.
Press "Park 3".
Enter the password (default is "456")
Press "#".
Press "1" for System Functions.
Press "4" for System Clock.
Enter the time in 12-hour format.
Press "#"
Press AM or PM by pressing "Park 3" in the LCD screen.
Press "#" to confirm.
Hang up or press "HF".

Date

Menu (F1)
Park 3 Key
Enter the Installer Password. 789 at Default.
Press # to confirm
Dial 9819
Enter the Month
Press # to confirm
Enter the Day
Press # to confirm
Enter the Year
Press # to confirm

Executone Isoetec IDS M-32 Phones:

Time

System must have the TIME option enabled. Time may be changed only from a designated Operator Phone.

- Lift the Handset.
- At the dial tone, dial "28" then the 4-digit time in military format. For example, "1500" = 3:00PM.
- A confirmation tone is heard.

